

35560 Grand River Ave, #420  
Farmington Hills, MI 48335  
P: 248-676-1007 / E: sales@z-checkcorp.com  
Website: www.z-checkcorp.com



**WITH  
INFRARED  
CAMERA**

# LEAKSHOOTER® LKS1000-V2T+IR

## Ultrasonic compressed air, gas and vacuum leak detection camera and thermal imager (IR).

Compressed air is a costly form of energy and 20 to 40% of it is lost through leaks.

Systematically checking for and eliminating leaks can therefore bring considerable energy savings.

Film, view and photograph the precise spot where compressed air, steam, pressurised gas and vacuums are leaking using the LEAKSHOOTER® LKS1000-V2T+IR.

The LEAKSHOOTER® LKS1000-V2T+IR is a sophisticated tool. Extremely sensitive, it is capable of finding all leaks, even the smallest, including those no bigger than the size of a syringe needle, at a distance of 20 metres. Leaks can be detected in all types of industrial environment thanks to the possibility of adjusting the gain on the device to filter out all undesirable noise.

The LEAKSHOOTER® LKS1000-V2T+IR is used like a camera. When it comes near a leak, a dynamic white target appears on the large colour screen. The target shrinks as it approaches the source of the leak. A bar graph at the bottom of the screen accompanies and facilitates the search.

When the device is facing the leak, a cross appears around the centre of the target. It is then possible to photograph and save the precise location of the leak.



APPROXIMATE SEVERITY OF  
**LEAK & FLOW & COST**  
(0-10) (m³/h) (€, \$, £)

VERY SMALL

SMALL

MEDIUM

BIG

VERY BIG



The photos can be uploaded directly onto a PC via a USB cable (supplied), ready to be attached to inspection reports.

It is still possible, whilst visually searching for a leak, to use the traditional method of leak detection, listening for the hissing sound of the leak using the professional headphones also supplied, which can be plugged directly into the device.

Embedded thermal IR camera (-10°C > +400°C) for T° analysis with Min.-Max.-Center cursors in full screen.

Various accessories are available for the LEAKSHOOTER® LKS1000-V2T+IR enabling it to be used for other applications as well as leak detection.

# ACCESSORIES



Detection in hard to reach areas with sensor:  
LKS FLEX – Flexible probe 400mm long  
LKS FLEX1500 – Flexible probe 1500 mm long



For Steam trap control:  
LKSPROBE  
Mechanical US Sensor




Tightness and sealing control:  
LKSDOME  
Ultrasonic emitter with 13 emitters



Laser pointer:  
LASERKIT – Autonomous laser kit + support for LEAKSHOOTER



Software:  
LEAKREPORTEDITOR – For report edition option



**Thermal Camera**  
 (160 x 120 pixels)  
 Min. - Max. - Central cursors  
 3 colors palettes



**LEAKREPORTEDITOR**  
 for report edition option  
 Available in different languages.



**LASERKIT option**  
 Autonomous laser kit  
 + support for LEAKSHOOTER



Photos (Leaks - Thermal)  
 CSV data file for reporting

**COMPRESSED AIR LEAK  
 DETECTION**



**COMPRESSED AIR LEAK  
 DETECTION**



**STEAM TRAP  
 INSPECTION**



**CORONA, PARTIAL  
 DISCHARGE DETECTION**









**VACUUM LEAK  
 DETECTION**





# SPECIFICATIONS LKS1000-V2T+IR

Sensitivity	Detects a leak of 0.1 mm at 3 bars at 20 m
Camera	Color 640 x 480 pixels + LED lighting
Thermal camera	FLIR LEPTON 160 x 120 px (14°F to +752°F) or (-10°C to +400°C), adjustable emissivity $\epsilon$ , sensitivity < 50 mK, frame rate 9 Hz
Display	Capacitive touchscreen - LCD Color 5,7" 640 x 480 pixels
Pictures	BMP, number, name, date and time
Dynamic target	White circle for leak detection Colored circle with cross for the leak severity
Measurements	dB RMS and MAX RMS & T° (°C or °F) - Min. - Max. - Center
Memory	Up to 1000 pictures, can be uploaded to PC (leaks and thermal)
Data export	CSV file with all leaks data for report editing
Communication	USB cable supplied
US sensor	Open type - Bandwidth $\pm$ 2 kHz to - 6 dB - Central frequency 40 kHz $\pm$ 1 kHz - Adjustable frequency mixer from 30 to 50 kHz - Adjustable gain from 40 to 106 dB
Headphones	Adjustable volume - Wired headphone LKSEAR
Power supply	Rechargeable Li-Ion battery
Autonomy	> 5 hours
Temperature range	- 10°C to + 50°C or (14°F to 122°F)
Dimensions	H : 310 mm - W : 165 mm - D : 65 mm
Weight	700 gr for the LKS1000 - 3.8 kg (8.4 lbs) including ABS case
CE Standards	CE Standards : EMC 2014/30/UE : EN61000-6-4 & EN61000-6-2
Accessories	<ul style="list-style-type: none"> <li> Ultrasonic emitter Reference : LKSDOME</li> <li> Flexible 400 mm US Sensor Reference : LKSFLEX</li> <li> Flexible 1500 mm US Sensor Reference : LKSFLEX1500</li> <li> Mechanical US sensor (steam trap - bearing) Reference : LKSPROBE</li> <li> Autonomous laser kit + support for LEAKSHOOTER. Option. Reference : LASERKIT</li> <li> LEAKREPORTEDITOR for report edition option. Available in different languages. Reference : LEAKREPORTEDITOR</li> </ul>



Distributed by :



35560 Grand River Ave, #420  
Farmington Hills, MI 48335  
P: 248-676-1007 / E: sales@z-checkcorp.com  
Website: www.z-checkcorp.com